

Letter of conformance

FOOD SAFE - EC1935/2004, EC 10/2011 conformity

Garlock GmbH Falkenweg1 41468 Neuss - GERMANY

We hereby confirm, our material

Garlock ePTFE Joint Sealant Tape Style 3535 mono-directionally expanded complies with the following regulations and laws in its current version as listed below:

- European Regulation (EC) No 1935/2004* with relevant requirements of regulation (EC) No 10/2011
- Foodstuffs, Consumer Goods and Animal Feed Code (Foodstuffs and animal feed code LFGB) with the relevant requirements of the German Consumer Goods Ordinance
- BfR memorandum on the examination of high polymers No.62
- FDA 21 CFR 177.1550 They meet ingredient and extract requirements. For products which have a self-adhesive backing, glue or adhesive tape is used which is, in accordance to our suppliers/raw-material-producers, conform to and meets the requirement of 21 CFR 175.105 for adhesives

The overall migration as well as the specific migration are below the legal limit values and in case of an application in accordance with the specifications.

Compliance with the overall migration limits for all type of foods testing to simulant A, B and D2 has been performed.

The following Substances with a limitation and/or specification are employed in the product mentioned above:

Substance	Limitation (SML)
1,3 Butadien (CAS 106-99-0) not detectable	smaller 0,05 mg/kg
Octadecyl-3-(3,5-di-tert-butyl-4-hydroxyphenyl) propionate (CAS 2082-79-3)	SML = 6mg/kg
2-Methyl-1,3-butadien (CAS 78-79-5) not detectable	Smaller 0,05 mg/kg

Thus, the ePTFE Joint Sealant Tape Style 3535 mono-directionally expanded may be used safely for gaskets which are used in the production of foodstuffs and may stand in direct contact with dry, aqueous, acid and fatty foodstuffs.

*This Material also is used within process and industries, which are not rated to EC1935/2004 and only is delivered with traceability under request within ordering process.

page 1 / 2

GARLOCK GMBH EnPro Industries family of companies Tel: +49 2131 349 0 Fax:+49 2131 349 222 www.garlock.com Garlock Sealing Technologies Garlock Rubber Technologies GPT Garlock PTY Garlock do Brasil

Garlock de Canada, LTD Garlock China Garlock Singapore Garlock USA Garlock India Private Limited Garlock de Mexico, S.A. De C.V. Garlock New Zealand Garlock Great Britain Limited Garlock Middle East



Specification regarding the intended use:

- Kind of foodstuffs or procedure for which the material is suitable:
 - o beverages: non-alcoholic and alcoholic drinks up to undenaturated ethyl alcohol
 - $\circ\,$ corn, cereal products, pastry products, biscuits, cakes and other baked goods, dry, fresh,
 - $\circ\,$ chocolate, sugar and products obtained from it, confectioneries, in solid and in past form,
 - $\circ\,$ fruit, vegetables and products obtained from it, in oily medium, in past or cream form, with a pH value of over 4,5
 - o fats and oils
 - o animal products and eggs with a pH value of over 4,5
 - dairy products with an pH value of over 4,5, milk products, natural cheese, preserved cheese, products
 - Various products: fried or roasted foodstuffs, preparations for the coocing of soups, stocks (liquid, solid or powder), fritters and the like, of animal origin, powdered or died, with fatty character, mustard, sandwiches, bread and pizza, any kind of foodstuff with fatty substances on the surface, Dried food with fatty surfaces, Cocoa paste, Spices and seasorning in oily media such as pesto, curry paste, concentrated extracts with an alcohol content of at least 6%, cacao, coffee, aromatic herbes, spices and condiments in a natural state and in oily medium, each with pH value of over 4,5
- Duration and temperature of the treatment and storage when in contact with the foodstuff
 - High temperature applications with dry, aqueous and fatty foodstuffs up to temperatures of 100°C and up to 121°C as well as long-term storage at room temperature and below
- Ratio between the surface in contact with the foodstuff and the volume, based on which the compliance of the material or article was determined.
 - o 6 dm² surface / 1 liter foodstuff

This letter of conformance represents the latest technical standard and has a unlimited validity.

It will be renewed in case of significant changes in composition or production that influence the migration of the material or if new scientific evidences emerge.

Garlock GmbH Falkenweg 1 41468 Neuss

Neuss, 22nd NOVEMBER 2017 R. Kulessa STATIC SEALS

*This Material also is used within process and industries, which are not rated to EC1935/2004 and only is delivered with traceability under request within ordering process.

page 2 / 2

GARLOCK GMBH EnPro Industries family of companies Tel: +49 2131 349 0 Fax:+49 2131 349 222 www.garlock.com Garlock Sealing Technologies Garlock Rubber Technologies GPT Garlock PTY Garlock do Brasil

Garlock de Canada, LTD Garlock China Garlock Singapore Garlock USA Garlock India Private Limited Garlock de Mexico, S.A. De C.V. Garlock New Zealand Garlock Great Britain Limited Garlock Middle East